

LYNCHBURG, VIRGINIA

SQ FT: 133,000

CERTIFICATION: ISO 9001

SHIPPING HOURS: 8am – 2pm

RECEIVING HOURS: 8am – 2pm

UNLOADING CAPABILITIES: Fork Side,
Overhead Crane



LEVELING LINE

60" ROWE LINE

48" Wide (.021"-.120")

60" Wide (.033"-.108")

240" Max Length

40,000# Max Coil Weight

10,000# Max Bundle Weight

Protection – 1 Sided PVC or Paper Interleave

RED BUD MULTI-BLANKING LINE

.020"-.135" Gauge Herr Voss Leveler

Slitting/Blanking Width: 5"-73"

Length: 14"-240"

Squareness: .015"

Length of Tolerance: +/- .015", over 60" +/- .030

50,000# Max Coil Weight

Protection-2 Sided PVC or 1 Sided Paper
Interleave

6K FIBER LASER (2)

TRUMPF TRULASER 5040 (2)

1" Maximum Thickness

2 Meter x 4 Meter Table

PRESS BRAKE

CINCINNATI PROFORM (2)

Up to 12 Feet of Bed Length

Up to 350 Tons

PUNCH PRESS

AMADA PUNCH & FIBER LASER COMBINATION

1" Maximum Thickness

MATERIAL HANDLING

CRANE: 36,000#

MAXIMUM FORKLIFT: 10,000#

SHEET LIFTER: 10,000#

QUALITY CONTROL

MEASURING EQUIPMENT

Romer Arm, Faro Arm, Quality Labs and
Measuring Tables

PROGRAMMING

Dedicated Team Committed to Accurate
and Reliable Programming (SolidWorks,
AutoCad, etc.)

ENGINEERING & INDUSTRIAL DESIGN

Metallurgical Engineering and Industrial
Design Expertise

PPAP / FIRST ARTICLE

Dedicated Team Focused on Successful
Implementation

PRODUCT TYPES

- Hot Rolled Pickled & Oiled
- Cold Rolled
- Galvanized
- Galvannealed
- Galvume
- Aluminized
- Electro Galvanized
- Pre Paint
- Stainless
- Aluminum
- Aluminum Tread